


LAMP PHOTOMETRIC REPORT

MODEL: 92EL62283065WH		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 3040.6 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1882	1877	1878	1881	1888	1894	1893	1888	0- 10	183.5	183.5	6.03
20	1679	1672	1674	1680	1695	1702	1699	1692	10- 20	505.6	689.0	22.7
30	1312	1299	1300	1311	1336	1349	1347	1336	20- 30	702.1	1391	45.8
40	810.9	797.9	798.8	810.9	831.9	848.0	844.8	831.8	30- 40	667.5	2059	67.7
50	409.8	404.0	401.4	408.8	424.6	431.5	433.4	425.4	40- 50	465.6	2524	83
60	197.4	193.4	191.1	196.0	201.4	205.7	204.6	203.2	50- 60	262.8	2787	91.7
70	117.0	112.4	108.7	114.7	119.6	119.0	115.1	117.7	60- 70	153.0	2940	96.7
80	46.75	41.46	37.09	42.86	46.42	45.34	41.45	45.15	70- 80	82.34	3022	99.4
90	0.8093	0.7952	0.7681	0.8044	0.7278	0.7080	0.7027	0.7078	80- 90	18.23	3041	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:06 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```