


LAMP PHOTOMETRIC REPORT

MODEL: 92FLCOM1040/WH		
POWER: W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 728.67 lm



$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%
10	969.7	968.1	981.0	1000	1022	1034	1008	981.4	0- 10	106.9	106.9	14.7
20	581.3	584.5	597.3	617.2	637.3	635.3	616.3	597.5	10- 20	218.5	325.4	44.7
30	334.8	343.1	349.1	353.4	353.5	346.0	337.9	332.2	20- 30	211.0	536.4	73.6
40	91.45	100.3	109.7	124.2	127.7	118.9	104.7	91.99	30- 40	152.0	688.4	94.5
50	10.29	10.71	10.52	11.72	10.78	10.63	9.782	9.926	40- 50	27.45	715.8	98.2
60	5.791	5.772	5.297	6.092	5.934	5.873	5.297	5.549	50- 60	6.921	722.8	99.2
70	3.150	2.978	2.525	3.283	3.267	3.112	2.678	2.928	60- 70	4.307	727.1	99.8
80	0.3689	0.2641	0.1685	0.2577	0.3684	0.2747	0.1912	0.2741	70- 80	1.508	728.6	100
90	0.0217	0.0190	0.0136	0.0150	0.0353	0.0340	0.0300	0.0341	80- 90	0.0998	728.7	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:  
Test Date:24 August 2022

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```