


LAMP PHOTOMETRIC REPORT

MODEL: 99PFMT30/BL		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1330.5 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	498.3	500.3	499.0	497.3	489.7	486.6	488.4	494.5	0- 10	47.74	47.74	3.59
20	467.4	470.4	469.4	464.3	452.2	445.1	448.7	458.9	10- 20	135.1	182.8	13.7
30	416.9	420.4	419.5	412.5	397.5	387.0	392.4	405.8	20- 30	200.2	383.1	28.8
40	353.1	356.5	355.6	348.4	331.6	318.9	325.1	341.1	30- 40	234.5	617.6	46.4
50	281.7	284.5	283.1	277.1	259.7	246.1	252.5	269.4	40- 50	236.0	853.6	64.2
60	206.5	208.2	206.7	201.4	185.5	172.1	177.8	194.7	50- 60	207.3	1061	79.7
70	129.7	131.9	131.0	125.6	112.5	100.3	105.0	120.1	60- 70	155.0	1216	91.4
80	58.12	60.39	61.19	55.36	44.94	35.94	39.62	51.30	70- 80	89.05	1305	98.1
90	3.787	3.363	8.893	2.776	2.307	0.9558	3.760	3.532	80- 90	25.54	1330	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 15 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

MODEL: 99PFMT30/BL		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

UNIT: cd

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 15 November 2022

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```